

PLCC Series

ET-3528J-111W

Datasheet

Features :

- High luminous Intensity and high efficiency
- Based on Blue/Green : InGaN, Red : AlGaInP technology
- Wide viewing angle : 120°
- Excellent performance and visibility
- Suitable for all SMT assembly methods
- IR reflow process compatible
- Environmental friendly; RoHS compliance

Typical Applications

- Signal and Symbol Luminaire
- Indoor and Outdoor Displays
- Backlighting (illuminated advertising, general lighting)
- Interior Automotive Lighting

Table of Contents

General Information	3
LED Package Dimension and Polarity	4
Absolute Maximum Ratings	5
Luminous Intensity Characteristics	5
Forward Voltage Characteristics	6
JEDEC Information	7
Reliability Test Items	8
Color Spectrum and Radiation Pattern	9
Optical and Electric Characteristics	10
Reflow Profile	11
Product Packaging Information	12
Precaution for Use	14
Forward Voltage Ranks	15
Luminous Intensity Ranks	15
Dominant Wavelength Ranks	15
Revision History	16
About Edison Opto	16

General Information

Introduction

Ultra high luminous efficacy, combined with the flexibility in design due to its slim and miniature size, PLCC LED Series are optimized to be used as lighting for signboard.

Product Nomenclature

The following table describes the available color, power, and lens type. For more flux and forward voltage information, please consult the Bin Group document.

Table 1. ET-3528J-111W series nomenclature

ET 3528 J - 1 1 1 W
X1 X2 X3 X4 X5 X6 X7

X1 LED Item		X2 Package		X3 Emitting Color		X4 Chip Quantity		X5~6 Serial No.		X7 Feature	
Code	Type	Code	Type	Code	Type	Code	Type	Code	Type	Code	Type
Edison	Top LED	3528	3.5X2.8mm	J	Cyan	1	1pcs			W	White surface

LED Package Dimension and Polarity




Figure 1. PLCC 3528 series Dimension




Figure 2. PLCC 3528 series circuit diagram

Notes:

1. All dimensions are measured in mm.
2. Tolerance : ± 0.20 mm

Absolute Maximum Ratings

The following table describe absolute maximum ratings of PLCC 3528 series.

Table 2 : Absolute maximum ratings for PLCC 3528 series

Parameter	Rating	Units	Symbol
Forward Current	30	mA	I_F
Pulse Forward Current ($t_p \leq 100\mu s$, Duty cycle=0.25)	100	mA	-
Reverse Current	10	uA	I_R
Reverse Voltage	5	V	V_R
Forward Voltage	3.7	V	V_F
Power Dissipation	110	mW	
LED Junction Temperature	115	°C	T_J
Operating Temperature	-30 ~ +85	°C	-
Storage Temperature	-40 ~ +100	°C	-
Soldering Temperature	255~260	°C	-
Manual Soldering at 350°C(Max.)	3	Sec	-

Notes:

1. Proper current derating must be observed to maintain junction temperature below the maximum at all time.
2. LEDs are not designed to be driven in reverse bias.
3. t_p : Pulse width time

Luminous Intensity Characteristics

The following table describes luminous Flux intensity of PLCC 3528 series.

Table 3 : Luminous intensity characteristics at $I_F=20mA$ and $T_a=25^\circ C$ for PLCC 3528 series

Part Name	Color	Luminous Intensity			Luminous Intensity Typ.(mcd)
		Min.	Typ.	Max.	
ET-3528J-111W	Cyan	700	850	--	2.5

Note: Luminous intensity is measured with an accuracy of $\pm 10\%$

Forward Voltage Characteristics

The following table describes forward voltage of PLCC 3528 series

Table 4 : Forward voltage characteristics at IF=20mA and Ta=25°C for PLCC 3528

Part Name	Color	V _F			Unit
		Min.	Typ.	Max.	
ET-3528J-111W	Cyan	2.8	--	3.7	V

Note: Forward Voltage is measured with an accuracy of $\pm 10\%$

JEDEC Information

JEDEC is used to determine what classification level should be used for initial reliability qualification. Once identified, the LEDs can be properly packaged, stored and handled to avoid subsequent thermal and mechanical damage during the assembly solder attachment and/or repair operation. The present moisture sensitivity standard contains six levels, the lower the level, the longer the devices floor life. PLCC 3528 series are certified at level 2a. This means PLCC 3528 series have a floor life of 4 weeks before PLCC 3528 series need to re-baked.

Table5. JEDEC characteristics for TS1003

Level	Floor Life		Soak Requirements			
	Time	Conditions	Standard		Accelerated Environment	
			Time (hours)	Conditions	Time (hours)	Conditions
2a	4 weeks	$\leq 30^{\circ}\text{C} / 60\% \text{ RH}$	696 +5/-0	$30^{\circ}\text{C} / 60\% \text{ RH}$	120 +1/-0	$60^{\circ}\text{C} / 60\% \text{ RH}$

Leve	Floor Life		Soak Requirements			
	Time	Condition	Standard		Accelerated Environment	
			Time (hours)	Condition	Time (hours)	Condition
1	Unlimited	$\leq 30^{\circ}\text{C} / 85\% \text{ RH}$	168 +5/-0	$85^{\circ}\text{C} / 85\% \text{ RH}$	-	-
2	1 year	$\leq 30^{\circ}\text{C} / 60\% \text{ RH}$	168 +5/-0	$85^{\circ}\text{C} / 60\% \text{ RH}$	-	-
2a	4 weeks	$\leq 30^{\circ}\text{C} / 60\% \text{ RH}$	696 ¹ +5/-0	$30^{\circ}\text{C} / 60\% \text{ RH}$	120 +1/-0	$60^{\circ}\text{C} / 60\% \text{ RH}$
3	168 hours	$\leq 30^{\circ}\text{C} / 60\% \text{ RH}$	192 ¹ +5/-0	$30^{\circ}\text{C} / 60\% \text{ RH}$	40 +5/-0	$60^{\circ}\text{C} / 60\% \text{ RH}$
4	72 hours	$\leq 30^{\circ}\text{C} / 60\% \text{ RH}$	96 ¹ +5/-0	$30^{\circ}\text{C} / 60\% \text{ RH}$	20 +5/-0	$60^{\circ}\text{C} / 60\% \text{ RH}$
5	48 hours	$\leq 30^{\circ}\text{C} / 60\% \text{ RH}$	72 ¹ +5/-0	$30^{\circ}\text{C} / 60\% \text{ RH}$	15 +5/-0	$60^{\circ}\text{C} / 60\% \text{ RH}$
5a	24 hours	$\leq 30^{\circ}\text{C} / 60\% \text{ RH}$	48 ¹ +5/-0	$30^{\circ}\text{C} / 60\% \text{ RH}$	10 +5/-0V	$60^{\circ}\text{C} / 60\% \text{ RH}$
6	Time on tabel (TOL)	$\leq 30^{\circ}\text{C} / 60\% \text{ RH}$	TOL	$30^{\circ}\text{C} / 60\% \text{ RH}$	-	-

Note:

The standard soak time includes a default value of 24 hours for semiconductor manufacturer's exposure time (MET) between bake and bag, and includes the maximum time allowed out of the bag at the distributor's facility.

Reliability Test Items

The following table describes operating life, mechanical, and environmental tests performed on PLCC 3528 series.

Table 6. Reliability Test 1

Stress Tes	Stress Conditions	Stress Duration	Failure Criteria
Temperature and Humidity	60°C / 60%RH	120 hours	No catastrophics
IR Reflow	Peak temp.=255~260°C*3 times	3 times	

Table 7. Reliability Test 2

Stress Tes	Stress Conditions	Stress Duration	Failure Criteria
Low Temperature Storage	-40°C	1000 hours	No catastrophics
High Temperature and high Humidity Storage	85°C / 85%RH	1000 hours	
Ambient Temperature Life	25°C, IF = 20 mA	1000 hours	
Temperature Cycle	-40°C/100°C, 30 min dwell <15min transfer	200 cycles	
Thermal Shock	-40 / 100°C, 15 min dwell<10 sec transfer	200 cycles	

Notes:

1. Reliability test 2 is performed after reliability test 1.
2. Depending on the maximum derating curve.
3. Failure Criteria:
 - Electrical failures
 - V_f Shift $\geq 10\%$
 - Luminous Intensity
 - I_v Decay $\geq 35\%$

Color Spectrum and Radiation Pattern

Emission Angle Characteristics

Table 8. Emission angle Characteristics at IF=150mA and Ta=25°C for PLCC 3528 series

Part Name	Color	2 $\theta_{1/2}$ (Typ.) Lambertian	Unit
ET-3528J-111W	-	120	Deg.




Figure 3: Beam pattern diagram for PLCC 3528 series




Figure 4: Wavelength & relative intensity for PLCC 3528 series

Optical and Electric Characteristics




Figure 5: Forward current & relative intensity for PLCC 3528 series




Figure 6 : Forward voltage & forward current for PLCC 3528 series

Reflow Profile

The following reflow soldering profiles are provided for reference. It is recommended that users follow the recommended soldering profile provided by the manufacturer of the solder paste used




Table 10. Table of Classification Reflow Profiles

Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Preheat & Soak		
Temperature min (T _{smin})	100°C	150 °C
Temperature max (T _{smax})	150°C	200 °C
Time (T _{smin} to T _{smax}) (t _s)	60-120 seconds	60-120 seconds
Average ramp-up rate (T _{smax} to T _p)	3°C/second max.	3 °C/second max.
Liquidous temperature (T _L)	183 °C	217 °C
Time at liquidous (t _L)	60-150 seconds	60-150 seconds
Peak package body temperature (T _p)*	230 °C ~235°C *	255 °C ~260 °C *
Classification temperature (T _c)	235°C	260 °C
Time (t _p)** within 5 °C of the specified classification temperature (T _c)	20** seconds	30** seconds
Average ramp-down rate (T _p to T _{smax})	6°C/second max.	6°C/second max.
Time 25°C to peak temperature	6 minutes max.	8 minutes max.

Notes:

* Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.

** Tolerance for time at peak profile temperature (t_p) is defined as a supplier minimum and a user maximum.

Product Packaging Information

Tapeing Reel




Figure 8 : Taping reel dimensions

• Packaging




Figure9 : Taping reel dimensions

• Package Label



EDISON OPTO CORPORATION

Customer P/N: XX-XXXXXXXX:XXXXX

P/N: XX-XXXXX-XXXX




Group: XX-XX-XX



Lot No: XXXXXXXX

QTY: xxxPCS




Color: XXXXXXXX

QC: _____

Figure10 : Package label

Table 11: Package dimensions and quantity

Item	Quantity	Total	Dimensions(mm)
Reel	2,000pcs	2,000pcs	Diameter=178
Inner box	5 reels	10,000pcs	240*235*67
Outer box	5 inner boxes	50,000pcs	353*254*256

Precaution for Use

Storage

1.1 Before opening the package

The LEDs should be kept at $<40^{\circ}\text{C}$ & $<90\%\text{RH}$. The LEDs should be used within a year. When storing the LEDs, moisture proof package with absorbent material (silica gel) is recommended.

1.2 After opening the package

The LEDs should be kept at $\leq 30^{\circ}\text{C}$ & $\leq 60\%\text{RH}$. The LEDs should be soldered within 4 weeks after opening the moisture proof package.

If unused LEDs remain, they should be stored in moisture proof packages, such as sealed containers with moisture proof package within absorbent material (silica gel). It is also recommended to return the unused LEDs to the original moisture proof package and to seal the moisture proof package again.

If the moisture absorbent material (silica gel) vapors or expires the expiration date, baking treatment should be performed by using the following conditions : 60°C for 20 hours.

The LEDs electrode and leadframe comprise a silver plated copper alloy. The silver surface may be affected by environments. Please avoid conditions which may cause the LEDs being corroded or discolored. The corrosion or discoloration might lower solderability or affect optical characteristics.

Please avoid rapid transition in ambient temperature, especially in high humidity environments where condensation can occur.

Static electricity

The products are sensitive to static electricity and highly taken care when handling them.


Static electricity or surge voltage will damage the LEDs. It is recommended to wear an anti-electrostatic wristband or an anti-electrostatic glove when handling the LEDs.

All devices, equipments and machinery must be properly grounded. It is recommended that measures be taken against surge voltage to the equipment that mounts the LEDs.

Pick and Place

Recommended conditions: Outer nozzle $> \phi 2.4 \text{ mm}$

*Avoid direct contact to the encapsulant with picking up nozzle. Failure to comply might result in pick and place processes or damage to encapsulant. In the worst cases, catastrophic failure of the LEDs due to wire deformation and/or breakage.



Notes:

All the information published is considered to be reliable. However, EDISON OPTO does not assume any liability arising out of the application or use of any product described herein.

EDISON OPTO reserves the right to make changes at any time without notice to any products in order to improve reliability, function or design.

EDISON OPTO products are not authorized for use as critical components in life support devices or systems without the express written approval from the managing director of EDISON OPTO.

Forward Voltage Ranks

Table12 : Forward voltage rank at IF=20mA and Ta=25°C

Color of Emission	Bin	Min	Max	Unit
Cyan	VG	2.8	3.1	V
	VH	3.1	3.4	
	VI	3.4	3.7	

Note:
Forward voltage measurement allowance is $\pm 0.1V$.

Luminous Intensity Ranks

Table13 : Luminous intensity rank at IF=20mA and Ta=25°C

Color of Emission	Bin	Min	Max	Unit
Cyan	J	500	600	mcd
	K	600	850	
	M	850	1,000	
	N	1,000	1,150	

Note:
Luminous Intensity Measurement Allowance is $\pm 10\%$

Dominant Wavelength Ranks

Table14 : Dominant Wavelength rank at IF=20mA and Ta=25°C

Color of Emission	Bin	Min	Max	Unit
Cyan	Y	500	505	nm
	Z	505	510	

Note :
Dominant Wavelength Measurement Allowance is $\pm 10\%$

Revision History

Table 15. Revision History of ET-3528J-111W.

Versions	Modification	Date
1	1. Establish a Datasheet.	2012/08/09

About Edison Opto

Edison Opto is a leading manufacturer of high power LED and a solution provider experienced in LDMS. LDMS is an integrated program derived from the four essential technologies in LED lighting applications- Thermal Management, Electrical Scheme, Mechanical Refinement, Optical Optimization, to provide customer with various LED components and modules. More Information about the company and our products can be found at www.edison-opto.com

Copyright©2012 Edison Opto. All rights reserved. No part of publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photo copy, recording or any other information storage and retrieval system, without prior permission in writing from the publisher. The information in this publication are subject to change without notice.

www.edison-opto.com

For general assistance please contact:
service@edison-opto.com.tw

For technical assistance please contact:
LED.Detective@edison-opto.com.tw